

IVCC Automotive Department Minimum Required Tool List

The tools listed below are minimum requirements. Students may purchase these tools from any vendor(s) that they want to. Students should check with the automotive instructors to find out how to contact the tool vendors, order their tools, and how much of a discount they can receive from them.

Art Koudelka 815-224-0220

Richard Marko 815-224-0252

Fax 815-224-0492

Fall 2023/Spring 2024/Summer 2024

Screwdrivers - (5 PCS)

1. 12" Straight Blade

4. 4" Phillips - #1 Tip

2. 9" Straight Blade

5. 6" Phillips - #2 Tip

3. 6" Straight Blade

Metric Combination Wrench Set - (17 PCS)

1. Metric Combination Wrenches - (8mm - 24mm)

1/4 Drive Metric Socket Set - (Standard and Deep - (6 Point) - (22 PCS)

- 1. 6mm, 7mm, 8mm, 9mm, 10mm, 11mm, 12mm, 13mm and 14mm Standard depth
- 2. 6mm, 7mm, 8mm, 9mm, 10mm, 11mm, 12mm, 13mm and 14mm Deep well
- 3. 1/4" Reversible Ratchet
- 4. 1/4" 2" and 4" Extensions
- 5. 1/4" Universal Joint

3/8" Drive Metric Socket Set -- (Standard and Deep) - (6 Point) (43 PCS)

- 1. 8mm, 10mm, 11mm, 12mm, 13mm, 14mm,15mm, 16mm, 17mm,18mm and 19mm Standard Depth
- 2. 8mm, 10mm, 11mm, 12mm, 13mm, 14mm, 15mm, 16mm, 17mm, 18mm and 19mm Deep well
- 5. 3/8" Reversible Ratchet
- 6. 3/8" 3", 6" and 12" Extensions
- 7. 3/8" Universal-Joint

Allen/Torx Socket Sets – Standard and Metric – (3/8" drive)

- 1. Standard Set 1/8", 5/32", 3/16", 7/32", 1/4", 5/16" and 3/8"
- 2. Metric Set 3mm, 4mm, 5mm, 6mm, 7mm, 8mm, 9mm and 10mm and 12mm)
- 3. Torx Socket Set T8, T10, T15, T20, T25, T27, T30, T40, T45, T50, T55 and T60
- 4. External Torx Set E4, E5, E6, E7, E8, E10, E12, E14, E16 and E18

Hammers - (2 PCS)

1. 26 oz. Ball Peen

2. Dead Blow Plastic hammer

Brake Tools - (3 PCS) - Required for ATO 2200 - Brake Systems

- 1. Hold Down Spring Tool
- 2. Return Spring Tools
- 3. Brake Pad Lining Gauge Set (recommend the Lisle 81850)

Toolbox & Miscellaneous Tools

- Toolbox
 Pocket flashlight
- Safety Glasses
 Tire inflator
- 3. Scraper 1" width 8. Tire Tread Depth Tool
- 4. 3-Jaw Oil Filter Wrench
- 5. 17mm, 19mm, 21mm, & 22 mm ½" Drive Deep Impact Sockets

Chisels and Punches - (5 PCS)

- 1. 3/8 Cold Chisel 4. 1/8 Pin Punch
- 2. 5/8 Cold Chisel 5. 3/16 Pin Punch
- 3. 3/8 Center Punch

Feeler Gauges - (2 PCS)

- 1. Spark Plug Gap Gauge .035" through .080"
- 2. Feeler Gauge 0.002" through 0.040"

Spark Plug Sockets - (3 to 6 PCS)

- 1. 5/8" Spark Plug Socket -- Flexible or Straight
- 2. 13/16" Spark Plug Socket Flexible or Straight
- 3. 9/16" Spark Plug Socket Flexible or Straight

Pliers - (5 PCS)

- 1. 6" Pair Needle Nose Pliers 4. 7" Straight Jaw Vise Grip Pliers
- 2. 7" Pair Heavy Diagonal Cutting Pliers 5. 10" Slip Joint Plier
- 3. 6" All Purpose Pliers

Electrical

- 1. 12-volt Test Light
- 2. Digital Multi-Meter (ask the electronics instructor about options)
- 3. Adjustable Ignition Spark Tester

Recommended but not required:

- 1. $\frac{1}{2}$ " Drive Torque Wrench, 50 250 foot/pounds
- 2. Standard Combination Wrenches (1/4" 3/4")
- 3. 3/8" Drive 8mm, 10mm, 11mm, 12mm, 13mm, 14mm, 15mm, 16mm, 17mm, 18mm and 19mm 12-point standard depth socket set
- 4. ½" Drive Ratchet, Breaker Bar, Universal Joint and 3", 6" & 12" Extensions
- 5. ½" Drive Metric standard depth socket set (10mm 24mm)